

JET250 G2 Self-Priming Pump

Suction head
9m

Liquid temperature
+40°C

Ambient temperature
+40°C

Max. Working pressure
4.8bar

Not suitable for
drinking water

Voltage fluctuation should
not exceed **10%** of rated value.

Basic Configuration

Mechanical sealing: ceramic / graphite / NBR rubber

Motor: two asynchronous motors, copper coils, built-in thermal protection, all closed fan-cooled, continuous operation

Protection: IP44

Insulation: Class B




1. Automatic rainwater / mains change over device
2. Automatic electronic pump controller to prevent run dry damage
3. Stainless steel pump body, corrosion resistant diffuser and impeller
4. Pump filter to remove the particles in the rainwater

Application

The Shimge Jet250 G2 is an automatic pressure pump with an inline filter and automatic changeover device. Mains water is connected to the changeover device as an automatic back up if the rainwater level is too low or if there is a power failure.

Ideal for household water supply to toilets, laundry and garden taps. Pump comes with a 2 year warranty.

Performance Curve



JET-G2

Model	Power		Max. Flow (m ³ /h)	Max. Head (m)	Head Range (m)	Max. Suction (m)
	kW	HP				
JET (S) 250G2	0.25	0.34	2.7	28	4~28	8
JET (S) 370G2	0.37	0.5	2.8	32	5~32	7
JET (S) 550G2	0.55	0.75	3.5	38	4~38	9
JET (S) 750G2	0.75	1	3.5	44	5.5~44	9
JET (S) 1100G2	1.1	1.5	4.2	48	9~48	9